HUMAN GROWTH HORMONE SUSTAINED RELEASE FINE PARTICLE PREPARATION AND METHOD FOR PRODUCING THE SAME

Publication number: JP2005008545

Publication date:

2005-01-13

Inventor:

OGAWA TAIRYO: IKOMA TOSHIYUKI: FUJII TAKAO:

MIYAMOTO YOKO; NIIMI JUN; TANAKA JUNZO

Applicant:

JAPAN SCIENCE & TECH AGENCY; OGAWA TAIRYO;

FUJII TAKAO; MIYAMOTO YOKO; NIIMI JUN; NAT

INST FOR MATERIALS SCIENCE

Classification:

- international:

A61K9/52; A61K9/16; A61K38/27; A61K47/02; A61K47/04; A61P5/10; A61K9/52; A61K9/16; A61K38/27; A61K47/02; A61P5/00; (IPC1-7): A61K38/27; A61K9/52; A61K47/02; A61K47/04;

A61P5/10

- european:

A61K9/16H2; A61K38/27

Application number: JP20030173410 20030618 Priority number(s): JP20030173410 20030618

Also published as:

EP1640019 (A1) WO2004112827 (A1) CN1791424 (A)

CA2524256 (A1)

Report a data error here

Abstract of JP2005008545

PROBLEM TO BE SOLVED: To provide a human growth hormone sustained release fine particle preparation which can avoid the employment of an organic solvent to the utmost, has both biodegradability and sustained release performance, sustains the release of the human growth hormone for three or more days, inhibits an initial burst release, can enhance the content of the human growth hormone to 10 % or more, can quantitatively adsorb and encapsulate the human growth hormone up to 20%, and has good dispersibility and needle passableness, and to provide a method for producing the same.

SOLUTION: This human growth hormone sustained release fine particle preparation is characterized by comprising a porous apatite derivative, the human growth hormone and a water-soluble divalent metal compound. The method for producing the human growth hormone sustained release fine particle preparation is characterized by stirring and dispersing fine porous apatite derivative particles in water containing the human growth hormone to infiltrate the aqueous solution in the porous apatite derivative, adding an aqueous solution containing the water-soluble divalent metal compound to infiltrate the water-soluble divalent metal compound in the porous apatite derivative, adding additives such as a stabilizer, and then lyophilizing or vacuum-drying the mixture.

COPYRIGHT: (C)2005, JPO&NCIPI

Data supplied from the esp@cenet database - Worldwide